## ReceiptNOW® Printers

## Teller Receipt Printers

ReceiptNOW printers add thermal receipt printing to your check scanner. Engineered to fit underneath Digital Check® SmartSource® or TellerScan® scanners, the stackable design allows users to combine their scanner and receipt printer into the desktop footprint of a single device.





#### **CUSTOMIZE** RECEIPTS

ReceiptNOW printers enable users to customize the look and feel of their receipts. Options include top and bottom logos, border messages, watermarks, and Windows TrueType fonts.

## STACKABLE DESIGN OPTIONS

ReceiptNOW printers are engineered to fit beneath your check scanner so you can enjoy a cleaner, more efficient workspace. ReceiptNOW is available in two form factors, each designed to fit beneath a range of SmartSource and TellerScan products.

## KEY FEATURES & BENEFITS

**DIGITAL** 

- USB and Optional Ethernet
   Connection Ports
- Modular Design Saves Counter Space
- Easy Slide-Out Drawer for Paper Replacement
- Economical and Easy Thermal Printing
- Print Graphics on Your Receipts
- Engineered for Durability

#### Compatibility

- USB or optional Ethernet interface
- Full 108 standard and international fonts with barcode
- Compatible with international power standards
- Worldwide certifications

## USB and/or Ethernet Connectivity

The ReceiptNOW printer offers flexibility for different environments. This printer includes options for both Ethernet and USB-connected configurations.

#### **Features**

- Quiet thermal receipt printer
- Frees up teller space
- Simple pull-out, drop-in paper
- Fits the largest receipt paper rolls
- Full or partial paper cut



# ReceiptNOW® Printers Configuration Options





## **ReceiptNOW Elite**

**USB** and/or **Ethernet** Configurations



#### **Part Numbers**

SRNELITE-USB (ReceiptNow Elite with USB)
SRNELITE-ETH2-E (ReceiptNOW Elite, USB and Ethernet)

#### **Supported Scanners**

- SmartSource Elite
- SmartSource Pro Elite
- SmartSource Pro Elite Plus
- SmartSource Expert Elite
- TellerScan TS500

## Ethernet Configuration Option for ReceiptNOW



(ReceiptNOW Rear View)

The ReceiptNOW Elite with Ethernet configuration is network-ready, and comes with two rear Ethernet ports, allowing you to connect the printer with

the Expert Elite (Ethernet) or Pro Elite Plus (Ethernet Convertible)

scanner on the same line.



## ReceiptNOW (original)

**USB** Configuration



#### **Part Numbers**

SRN2PTR-USB (ReceiptNow original with USB)

#### **Supported Scanners**

- SmartSource Professional
- TellerScan TS240



## ReceiptNOW® Printers



## **Specifications**

#### **Printer Dimensions**

#### ReceiptNOW Elite

Height: 5.7 in (14.48 cm) Width: 5.3 in (13.46 cm) Length: 10.5 in (26.67 cm)

#### ReceiptNOW (original)

Height: 5.4 in (13.72 cm) Width: 6.1 in (15.5 cm) Length: 15.3 in (38.86 cm)

#### Printing / Feed / Cut

Direct Thermal Printer Maximum print speed is 250mm/sec. (ReceiptNOW Elite) Resolution: 203 x 180 dpi 95 Alphanumeric, 13 International Characters with Kanji TrueType Fonts available when being driven as a Windows printer 1D/2D Bar Code Fonts 512K On-board Logo Flash Full/Partial Auto Cutter

#### **Controls**

On/Off Switch Paper Empty/Low LEDs with audible alerts Paper Feed Button Paper Width Adjustment Power Indicator

#### Paper / Loading

Standard, Security, Non-BPA, 2-color Paper Paper Widths: 2.4 in to 3.25 in (6.1 cm to 8.3 cm) Paper Roll Diameter: 3.25 in (8.3 cm) Slide Out Tray, Drop-in Paper

#### Interface

USB and/ or Ethernet (ReceiptNow Elite) USB only (ReceiptNow Original) Standard ESC/POS Command Set OPOS & JavaPOS, Auto Status Back (ASB)

#### **Included Accessories**

USB 2.0 cable (ReceiptNow Elite USB or Ethernet & ReceiptNow (original)) 1 ft. Ethernet cable (ReceiptNow Elite Ethernet) International 100-240VAC, 50/60Hz power supply

#### **Graphic Receipt Customization**

Multiple Graphics Can be Placed Anywhere Custom Messages Watermarks

#### **Supported Operating Systems**

Windows 11, Windows 10 (32/64 bit)

#### **Environmental**

Operating Temperature: 41° - 104° F (5° - 40° C) Operating Humidity: 20 - 90% non-condensing

#### Certifications

**Safety:** UL, cUL, CE

#### **Emissions:**

FCC: Class B ICES-003 CE VCCI

#### Power Supply Efficiency:

DOE Level VI

RoHS Compliant

#### **Part Numbers**

SRNELITE-USB (ReceiptNOW Elite with USB) SRNELITE-ETH2-E (ReceiptNOW Elite, USB and Ethernet) SRN2PTR-USB (ReceiptNOW Original with USB)

