

# SmartSource® Elite 55

## The Secure Choice®



Digital Check's SmartSource Elite 55 check scanner is designed with the remote deposit capture operator in mind. The robust, low-maintenance design and ease of use ensure a positive experience for users. The Elite 55 can also be used as a lower-cost alternative for teller installations that only require single-line endorsement or are utilizing virtual endorsement.



### SINGLE-LINE ENDORSEMENT

The SmartSource Elite 55 is configured with a highly flexible single-line rear inkjet endorser for remote deposit capture applications with an endorsement requirement. Endorsement text can be customized based on bank or application provider preference.



### ID CARD SCANNING

Features two-sided ID card capture using 600 dpi image sensors that produce high-resolution color or grayscale images.



### AUTOMATED CLEANING

An indicator light alerts users when it is time to clean. Use the Smart Button to activate cleaning mode, insert a cleaning card, and the scanner performs a unique cleaning sequence that scrubs the track and cleans the sensors.

### KEY FEATURES & BENEFITS

- **Batch Feed - Scans up to 55 DPM**
- **Single-Line Inkjet Endorser**
- **Automated Cleaning with Smart Button Indicator**
- **ID Card Scan**
- **600 dpi Image Sensors**
- **E13B and CMC7 MICR Recognition with Auto-Detect and integrated E13B Optical Recognition Assist**



### Ideal for Remote Deposit Capture

The SmartSource Elite 55 scanner has been optimized for remote deposit capture applications. With a processing speed of 55 documents per minute and a 100-document auto-feeder, the Elite 55 scanner quickly processes batches of documents.



### Quality & Performance

The Elite 55 is based on the proven design of the SmartSource Pro Elite, continuing a reputation for accuracy and reliability. The Elite 55 is an affordable multi-feed check capture option that doesn't compromise on the quality and performance you expect from a Digital Check® product.



### Industry Leading Image & MICR Capture

The Elite 55 uses 600 dpi image sensors and applies thresholding to create high-resolution images, resulting in superb CAR/LAR read rates. Our top-of-the-line MICR read heads coupled with optical recognition offer a proven and reliable defense against ambiguous characters and out-of-spec documents.



# SmartSource® Elite 55

## Scanner Specifications



### Scanner Dimensions

Height: 6.99 in (17.8 cm)  
Width: 5.93 in (15.06 cm)  
Length: 8.66 in (22 cm)  
Weight: 4.7 lbs. (2.1 kg)

### Scan Speeds - Documents Per Minute (DPM)

Up to 55 DPM

### Document Input and Output Pockets

Entry Pocket: Up to 100-item hopper capacity  
Entry pocket automatically opens for ease of use  
Double-feed document detection  
Exit Pocket: Up to 150 items

### Document Handling

Document Height: 2.00 to 6.00 in (5.08 to 15.24 cm)  
Image Capture Height: Up to 4.25 in (10.80 cm)  
Document Length: 2.90 to 9.25 in (7.37 to 23.5 cm)  
Document Weight: 16 to 28 lb (60 to 105 gsm)  
Document Thickness: 0.0032 - 0.0058 in (0.081 - 0.147 mm)  
Front ID Input: ID cards and items up to 3.375 x 2.25 in (85.60 x 57.15 mm)  
ID Card Capture (supported by application)

### Inkjet Endorser Option

User-replaceable ink cartridge (96 dpi printing, 1-line)  
Three (3) levels of print quality available (economy, standard, or premium)  
User-programmable text

### Image Sensors

Resolution: 600 dpi  
Light Source: Tri-Color LEDs

### Image Capture

Two (2) color images or a combination of up to five (5) bitonal and gray

#### Image renditions available

- Bitonal (black/white)
- Gray level (256 gray shades)
- Color (24-bit, RGB)

#### Image resolutions available

- 300 dpi, color only (reduced throughput)
- 240, 200 dpi, gray level or bitonal
- 120, 100 dpi, gray level

### Image Compression Standards

CCITT Group 4 (bitonal images)  
JPEG Baseline (gray level images)  
Uncompressed 24-bit, RGB pixel data (color images)\*

### Part Numbers

SSM1-ELITE55 (Elite 55 standard model)  
SSM1-ELITE55-IJ (Elite 55 with inkjet endorser)

### MICR/OCR Recognition

E13B and CMC7 auto-sensing  
OCR-A, OCR-B, E13B  
Two (2) 0.50-inch OCR scan bands provided  
96 characters per scan band  
MICR/OCR combine read

### Productivity Functions (Smart Button)

Multi-colored LED status light, combined power switch, feeder start/stop, clear document jams, and activate cleaning mode

### Connectivity

High-speed USB 2.0 cable and power supply included

### Application Programming Interfaces (API)

SmartPVA API  
DeviceSuite API  
Ranger Transport API (purchased separately from Silver Bullet Technology Inc.)

### Supported Operating Systems

#### SmartPVA API

Windows 11, Windows 10 (32/64 bit)

#### DeviceSuite

Windows 11, Windows 10 (32/64 bit)

**Ranger Transport API** (Please contact Silver Bullet Technology Inc. directly for information about Ranger's supported operating systems)

### Standard Warranty

One year pursuant to Digital Check Corp.'s limited product warranty

### Power Requirements

100-240 VAC @ 50/60 Hz  
Operating Power: 48 W  
Standby Power: 3 W

### Environmental

Operating Temperature: 60° - 90° F (15° - 32° C)  
Operating Humidity: 35 - 85% non-condensing

### Certifications

#### Safety:

UL, cUL, CE, BIS

#### Emissions:

FCC: Class A  
ICES-003  
CE  
VCCI

### Power Supply Efficiency:

DOE Level VI

RoHS Compliant



## Stackable Receipt Printer Option

Digital Check offers the ReceiptNOW® Elite thermal printer, designed to fit underneath the Elite 55 to minimize overall space requirements.

